DIALOG(R) File 351:DERWENT WPI (c) 1999 Derwent Info Ltd. All rts. reserv.

004719550

WPI Acc No: 86-222892/198634 XRAM Acc No: C86-096141 XRPX Acc No: N86-166305

Fire extinguishing agent - comprises high water absorption resin,

phosphorus and water

Patent Assignee: MORITA PUMP KK (MORI-N)

Number of Countries: 001 Number of Patents: 002

Patent Family:

Patent No Kind Date Week
JP 61154578 A 19860714 198634 B
JP 92051188 B 19920818 199237

Local Applications (No Type Date): JP 84281575 A 19841226; JP 84281575 A

19841226

Priority Applications (No Type Date): JP 84281575 A 19841226

Abstract (Basic): JP 61154578 A

The agent (1) contains high water-absorbing resin and phosphorus, except white phosphorus, which are added to the water.

The high water-absorbing resin has water absorption magnification (weight after absorption of water/weight before absorption of water) of 500 or more. The resin is added in amt. of 0.1-2 pts. wt. per 100 pts. of water.

USE/ADVANTAGE - (1) is effective in prevention of damage due to water and excellent in fire extinguishing power, esp. for fire of wood material. Since the phosphorus, except white phosphorus is added, (1) has excellent cooling effect, air intercepting effect, and water damage preventing effect. The water absorbing property of the resin is maintained, with flame shielding property combined. Thus, (1) has both effects of fire extinguishing power, flame shielding and water damage prevention.

(6pp Dwg.No.0/0)